

UNCLASSIFIED

AD NUMBER	
AD303146	
CLASSIFICATION CHANGES	
TO:	unclassified
FROM:	confidential
LIMITATION CHANGES	
TO: Approved for public release; distribution is unlimited.	
FROM: Distribution authorized to U.S. Gov't. agencies and their contractors; Administrative/Operational Use; JAN 1959. Other requests shall be referred to Feltman Research and Engineering Labs., Picatinny Arsenal, Dover, NJ.	
AUTHORITY	
ARRADCOM ltr 6 Jul 1981; ARRADCOM ltr 6 Jul 1981	

THIS PAGE IS UNCLASSIFIED

AD-303146

RIA-81-U570

USADACS Technical Library



5 0712 01013687 6

02590220

TECHNICAL
LIBRARY

C-8

TECHNICAL REPORT 2586

AD 303146

DEVELOPMENT OF XM5E2 AND XM10 GUIDED MISSILE WARHEADS (U)

BRIAN D. WALTERS

Regraded

Unclassified

By authority of

DTIC (AD 303 146)

Date

6 July 81

JANUARY 1959

EXCLUDED FROM GENERAL
DECLASSIFICATION SCHEDULE



FELTMAN RESEARCH AND ENGINEERING LABORATORIES
PICATINNY ARSENAL
DOVER, N. J.

ORDNANCE PROJECT TU1-3050

DEPT. OF THE ARMY PROJECT 516-04-006

COPY 41



DISPOSITION

When this report is no longer needed, Department of Defense agencies should destroy it in accordance with AR 380-5. All others should return the report to Technical Information Section, Picatinny Arsenal, Dover, N. J.

ADDITIONAL COPIES

Requests for additional copies of this report should be made to Armed Services Technical Information Agency, Arlington Hall Station, Arlington 12, Virginia.

REPRODUCTION

Reproduction of this document, in whole or in part, is prohibited except with permission of the issuing office; however, ASTIA is authorized to reproduce the document for United States Governmental purposes.

AD- 303146

SECURITY REMARKING REQUIREMENTS

DOD 5200.1-R, DEC 78

REVIEW ON 28 JAN 79

THIS REPORT HAS BEEN DELIMITED
AND CLEARED FOR PUBLIC RELEASE
UNDER DOD DIRECTIVE 5200.20 AND
NO RESTRICTIONS ARE IMPOSED UPON
ITS USE AND DISCLOSURE.

DISTRIBUTION STATEMENT A

APPROVED FOR PUBLIC RELEASE
DISTRIBUTION UNLIMITED.

UNCLASSIFIED

AU 005 146

CLASSIFICATION CHANGED
TO: UNCLASSIFIED
FROM: CONFIDENTIAL
AUTHORITY:
ARRADCOM LLC
13 FEB 2008



UNCLASSIFIED

UNCLASSIFIED

DTIC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. BFN551

AD- 303 146 16/3

apn 81

PICATINNY ARSENAL DOVER N J

DEVELOPMENT OF XM5E2 AND XM10 GUIDED MISSILE
WARHEADS

(U)

DESCRIPTIVE NOTE: Technical rept.,
JAN 59 27P WALTERS, BRIAN D.;
REPT. NO. PA-TR-2586
PROJ: ORD-TU1-3050

UNCLASSIFIED REPORT

C-8320

DESCRIPTORS: *FRAGMENTATION AMMUNITION, *GUIDED
MISSILES, BLAST, FLIGHT TESTING, FRAGMENTATION, TESTS,
WARHEADS

(U)

CONFIDENTIAL

DDC REPDRT BIBLIDGRAPHY SEARCH CNTRDL NO. BFO20E

AD- 303 146 16/3
PICATINNY ARSENAL DDVER N J

aug 78

DEVELOPMENT DF XM5E2 AND XM10 GUIDED MISSILE
WARHEADS

(U)

DESCRIPTIVE NDTE: Technical rept.,
JAN 59 27P WALTERS, BRIAN D.;
REPT. ND. PA-TR-25B6
PROJ: ORD-TU1-3050

EXCL. CDNFIDENTIAL REPORT

DESCRIPTORS: *FRAGMENTATION AMMUNITIDN, *GUIDED
MISSILES, BLAST, FLIGHT TESTING, FRAGMENTATION, TESTS,
WARHEADS

(M)

~~CONFIDENTIAL~~

DEVELOPMENT OF XM5E2 AND XM10
GUIDED MISSILE WARHEADS (U)

by

Brion D. Walters

January 1959

This document contains information affecting the national defense of the United States within the meaning of the Espionage Laws, Title 18, U. S. C., Sections 793 and 794. The transmission or the revelation of its contents in any manner to an unauthorized person is prohibited by law.

Feltman Research and Engineering Laboratories
Picatinny Arsenal
Dover, N. J.

Technical Report 2586

Ordnance Project TU1-3050

Dept of the Army Project 516-04-006

Approved



V. LINDNER
Chief, Missile Warhead
and Special Projects
Laboratory

~~CONFIDENTIAL~~

TABLE OF CONTENTS

	Page
Object	1
Summary	1
Conclusions	1
Recommendation	1
Introduction	1
Description of the Warheads	2
Test Results	2
Static Functioning Tests	3
MIL-STD Tests	3
Packing Tests	5
Missile Flight Tests	5
References	6
Distribution List	26
Figures	
Fig 1 Loading Assembly of XM5E2 Guided Missile Warhead	7
Fig 2 Inert Parts Assembly of XM5E2 Guided Missile Warhead	8
Fig 3 Detail of XM5E2 Guided Missile Warhead	9
Fig 4 Molded Phenolic Plug for the XM10 Warhead	10
Fig 5 Detail of XM5E2 Guided Missile Warhead	11

TABLE OF CONTENTS

	Page
Fig 6 Loading Details of XM5E2 Guided Missile Warhead	12
Fig 7 Details of XM5E2 Guided Missile Warhead	13
Fig 8 Details of XM5E2 Guided Missile Warhead	14
Fig 9 Details of XM5E2 Guided Missile Warhead	15
Fig 10 Details of XM5E2 Guided Missile Warhead	16
Fig 11 Loading Assembly of XM10 Inert Guided Missile Warhead	17
Fig 12 Ammunition Packing Crate for XM5E2, XM9, and XM10 Guided Missile Warheads (Sheet 1)	18
Fig 13 Ammunition Packing Crate for XM5E2, XM9, and XM10 Guided Missile Warheads (Sheet 2)	19
Fig 14 Ammunition Packing Crate for XM5E2, XM9, and XM10 Guided Missile Warheads (Sheet 3)	20
Fig 15 Field Setup for Static Functioning Tests	21
Fig 16 External View of Field Setup	22
Fig 17 Internal View of Field Setup Showing Warhead Positioned in Missile Compartment	23
Fig 18 Typical Fragment Pattern on Mild Steel Plates Located at 15 Feet	24
Fig 19 Initial Fragment Velocity for XM5 Warhead with Missile Components	25

~~CONFIDENTIAL~~

OBJECT

To design and develop blast-fragmentation and training warheads for use with the Hawk missile.

military requirements established by OCM 34681, dated 9 April 1953.

b. The XM5E2 warhead is suitable for use in the Hawk missile system.

SUMMARY

The XM5E2 warhead is a 110-pound blast-fragmentation warhead designed and developed by Picatinny Arsenal for use in the Hawk missile against aircraft. The warhead, which is barrel shaped, contains approximately 73 pounds of H-6 explosive. It is initiated by the XM32E2 safety and arming device.

Development tests of the warhead gave satisfactory results. These tests included static functioning, drop, and storage tests at Aberdeen Proving Ground, centrifuge and vibration tests at Picatinny Arsenal, and missile flight tests at White Sands Missile Range.

The XM10 warhead is essentially an inert training version of the XM5E2 warhead. Because it is inert, no special tests of the XM10 were conducted.

Packing crate designs were prepared, and crates manufactured and tested at Picatinny Arsenal. The warhead designs were then released by Army Rocket and Guided Missile Agency for production engineering, and manufacture of user test quantities.

CONCLUSIONS

a. The XM5E2 and XM10 warheads and packing designs as developed meet

RECOMMENDATION

It is recommended that production engineering work on the XM5E2 and XM10 warheads continue.

INTRODUCTION

1. Studies were conducted by the Ballistic Research Laboratories, at the direction of the Ordnance Office, to determine design parameters for the XM5-type warhead. The parameters selected were:

Charge-to-metal ratio	3
Fragment size, grains	120
Fragment beam angle	$\pm 30^\circ$
Explosive	H-6

The warhead was to be primarily a blast type, with fragmentation secondary, in order to cause structural kills of any type aircraft.

2. In February 1955, Redstone Arsenal (now Army Rocket and Guided Missile Agency) requested Picatinny Arsenal to

~~CONFIDENTIAL~~

design and develop the XM5-type warhead based on results of the Ballistic Research Laboratories studies (Ref 1). Because of the high charge-to-metal ratio, the weight of purely structural parts had to be held to a minimum. Plastic materials were therefore used for as many of the warhead components as possible. Following completion of initial designs, a series of development tests were conducted which included static functioning, drop, storage, centrifuge, vibration, and missile flight tests.

3. In April 1957, Picatinny Arsenal was assigned responsibility for design and development of the XM10 warhead (Ref 2). The XM10 was to simulate the XM5E2 warhead for use in training of personnel.

DESCRIPTION OF THE WARHEADS

4. The XM5E2 and XM10 warheads are barrel shaped, 13 inches long, and 13.38 inches in diameter. Their inert parts assemblies weigh approximately 37 pounds and are identical, with one exception. The plug in the XM5E2 warhead is drilled to accept two RDX leads which form a part of the explosive train of that design (Figs 3, 4, & 6, pp 9, 10, and 12). The various components of the assemblies are bonded with polyester or epoxy resin mixtures.

5. The inner body assembly consists of an aluminum fore plate and locator pin well and a glass-reinforced-plastic inner body and aft plate (Figs 7, 8, and 10, pp 13, 14, and 16). To this assembly is bonded a molded phenolic S & A liner

assembly (Figs 5 and 7, pp 11 and 13) containing a molded phenolic plug for the XM10 (Fig 4) or booster extension for the XM5E2 (Fig 3). Fragments are bonded to the outer surface of the inner body and are covered by a glass-reinforced-plastic outer body (Fig 2, p 8).

6. The S & A liner assembly contains threaded inserts which are used to secure an XM32E2 safety and arming device. This device initiates two RDX leads in the booster assembly (Fig 6) which in turn initiate a centrally located RDX booster. The booster initiates the 73-pound bursting charge of H-6 explosive (Fig 1, p 7). The XM10 warhead contains an inert filler in lieu of these explosive components (Fig 11, p 17). After loading, a glass-reinforced-plastic closing plug (Fig 7) is bonded over the loading hole in the fore plate.

TEST RESULTS

7. A series of fragmentation tests were conducted using approximately 120-grain configurations. The following size fragments were tested (dimensions given in inches):

.50 × .50 × .25

.522 × .522 × .221

.668 × .668 × .135

.674 × .674 × .133

.528 × .528 × .218

For each test, nine fragments were sandwiched between two .06-inch-thick glass-reinforced-plastic sheets. The

fragment sandwich was positioned in front of a 4.2-inch-high by 1.5-inch-diameter cylinder of H-6 explosive. After the charge was initiated by an RDX booster and blasting cap, fragments were recovered from a stack of 4 x 8 foot cardboard sheets and weighed. It was concluded from these tests that .50 x .50 x .25 inch fragments should be used in the warhead since these exhibited the least breakup and weight loss (Ref 3).

8. An investigation was made to determine whether or not RDX leads in the booster extension would initiate the bursting charge before initiating the centrally located booster cup assembly. The leads were initiated and the resultant detonation photographed using a camera running at 25 frames in 20 microseconds. It was concluded from these tests that the leads would initiate the booster, as intended, before their detonation waves propagated through the sides of the booster extension.

9. Following the above tests of components, 28 warheads were fabricated and used for development tests as follows:

Static functioning tests	6
MIL-STD tests	15
Packing tests	2
Missile flight tests	5

Static Functioning Tests

10. Each warhead was positioned on top of a 10-foot-high pedestal located in the center of an arena of 15 feet radius.

The arena consisted of mild steel plates and blast gages as shown in Figures 15, 16, and 17 (pp 21, 22, and 23). The centers of the plates and blast gages were also positioned 10 feet above the ground. Measurements were made of the free-air blast and the mass, spatial, and velocity distribution of warhead fragments (Figs 18 and 19, pp 24 and 25).

11. Two XM5 warheads were tested in the as-received condition. The remainder (2 XM5, 2 XM5E1) were positioned inside a missile compartment. A water tank simulating the mass of the missile guidance package was positioned at the forward end of the compartment.

12. From these tests, it was concluded that the missile skin causes a 350 fps, or 5%, loss in average fragment velocity through the missile skin and that the warhead produces an average side-on free-air peak blast pressure of approximately 42.3 psi at a distance of 20 feet (Ref 4).

MIL-STD Tests

13. Safety drop tests from a 40-foot height were conducted at Aberdeen Proving Ground. One warhead impacted on its forward end, the second impacted on the S & A cavity, and the third impacted on a mounting lug on its fore plate. Since there was no evidence of detonation on or after impact of each warhead, it was concluded from these tests that the warhead is drop safe (Ref 5).

14. A total of 6 storage tests were conducted at Aberdeen Proving Ground.

In the first series of tests two XM5E1 warheads were subjected to 30-day storage tests at 180°F. That temperature was used instead of 160°F at the direction of Army Rocket and Guided Missile Agency, based on temperatures expected at that time to be encountered during the missile-ready period on the launcher. Both tests were stopped after 140 hours because 2.88 and 3.8 pounds of explosive had exuded from the respective warheads. One of these warheads was then dropped from a height of 40 feet with no resultant detonation. The second was statically detonated to provide more blast and fragmentation data (Ref 6).

15. Two additional XM5E1 warheads were subjected to two 14-day JAN cyclic temperature and humidity tests except that the upper temperature limit was increased from 160°F to 180°F for reasons stated above. One test was stopped after 143 hours due to the exudation of 1.8 pounds of explosive. When dropped from a height of 40 feet this warhead did not detonate. The second test was stopped after 189 hours due to the exudation of 3.31 pounds of explosive. This warhead was statically tested to obtain additional blast and fragmentation data (Ref 6).

16. Based on further missile tests conducted by Raytheon Manufacturing Company, the prime missile contractor, it was concluded that the warhead would not be subjected to temperatures in excess of 160°F. Subsequently, one XM5E2 warhead was subjected to two 14-day JAN cyclic temperature and

humidity tests, and a second XM5E2 was stored for 30 days at 160°F. The warhead subjected to the cyclic storage test successfully passed the test since no exudation of explosive was observed and the components were not damaged. However, a small amount of explosive exuded from the warhead stored for 30 days at 160°F (Ref 7). On the basis of a subsequent investigation conducted at Picatinny Arsenal, it was decided to add 0.5% of Micro-Cel E to the H-6 explosive to prevent further exudation.

17. One XM5 warhead was centrifuge-tested at Picatinny Arsenal. During the test, two lugs of the fore plate delaminated when 30 "g's" was applied in the aft direction. To strengthen the lugs, the plastic laminate was sandwiched between steel plates, which were held together by cap screws. Warheads with these metal-reinforced lugs were designated XM5E1.

18. An inert-loaded XM5E1 warhead successfully passed additional centrifuge tests in which 50 "g" loads were applied in aft and lateral directions (Ref 8). Subsequently, however, the fore plate material was changed from a glass-reinforced-plastic laminate to aluminum to eliminate tolerance difficulties and to make the warhead stronger. Warheads with this aluminum fore plate were designated XM5E2. The change necessitated repeating the 50 "g" centrifuge test. One XM10 warhead (an inert-loaded XM5E2) successfully withstood the 50 "g" loads applied aft and laterally (Ref 9).

19. One XM5E1 warhead successfully withstood vibration tests. During these tests a 30-minute resonant search was conducted using vibrations of 30 to 2000 cps at ± 6 "g" accelerations. The warhead was then vibrated for 10 minutes at each resonant frequency detected (Ref 10). Because of the change to an aluminum fore plate described in the previous paragraph, the vibration tests were repeated with an XM10 warhead. The vibration schedule was revised in accordance with later information received from Raytheon Manufacturing Company as follows:

a. 10 to 150 cps at ± 4 "g" accelerations

b. 150 to 400 cps at ± 6 "g" accelerations

c. 400 to 2000 cps at ± 8 "g" accelerations

As before, the warhead was vibrated for 10 minutes at each resonant frequency detected. It was not damaged (Ref 11).

20. An internal pressure test was made to determine the failure point of an XM5 warhead inert parts assembly. It was found that the S & A liner fractured under an air pressure of 15 to 20 psi gage (Ref 12).

Packing Tests

21. Satisfactory results were obtained from rough handling tests of the warhead packing crate. A crate containing 2 inert-loaded XM5 warheads was

subjected to 1 drop from a height of 2 feet onto each of 2 diagonally opposite corners of the base and 1 horizontal drop from 2 feet onto the 2-inch edge of a 2 x 4 timber. Neither warhead was damaged.

Missile Flight Tests

22. Three XM5E1 and two XM5E2 warheads were successfully flown in Hawk missiles. In each of the three cases where the missile functioned properly, there resulted "K" kills of QF-80 or QB-17 drones. Because of missile malfunctions, two of the warheads did not reach their target. However, one of these latter two was successfully initiated by the missile destruct system. No destruct command reached the other, and it did not detonate, even after impacting the ground. These tests demonstrated the compatibility of the warhead and fuze system and the ability of the warhead to be safely flown in the Hawk missile.

23. Additional flight tests using industrially furnished XM5E2 warheads are continuing. Out of 4 such additional tests, all have resulted in "K" kills of target drones.

24. On the basis of satisfactory performance during static functioning, MIL-STD, packing, and missile flight tests, the XM5E2 and XM10 warheads were released for production engineering and manufacture of user test quantities (Ref 13).

~~CONFIDENTIAL~~

REFERENCES

1. Ltr, ARGMA to PA, dtd 25 Feb 55,
ORDDW-MTTW 471.9 (C)
2. Ltr, ARGMA to PA, dtd 26 Apr 57,
ORDDW-GMT-W 471.9
3. PA Proof Testing Lab Report 61-209,
dtd 27 Dec 55
4. BRL Tech Note 1170, dtd Jan 58
5. APG Firing Record B-14089
6. D&PS Firing Record B-14142
7. D&PS Report DPS/TU1-3050A/1,
dtd May 58
8. PA Firing Record, J. O. TR 487-57,
dtd 4 June 57
9. PA Firing Record, J. O. TR 391-58,
dtd 13 May 58
10. PA Firing Record, J. O. TR 487-57,
dtd 7 May 57
11. PA Experimental Test Report,
test No. 29-58, dtd 7 May 58
12. PA Materials Testing Lab Report
69-57-281
13. 1st Ind, ARGMA to PA, dtd 19 Aug 58,
to Ltr PA to ARGMA, dtd 16 Jul 58,
ORDBB-TF3-470.TU1-3050A, F,
ORDXR-RTM 471.9

~~CONFIDENTIAL~~

CONFIDENTIAL

REF ID: A66509

CONFIDENTIAL

F




Fig 1 Loading Assembly of XM5E2 Guided Missile Warhead

CONFIDENTIAL




Fig 2 Inert Parts Assembly of XM5E2 Guided Missile Warhead







Fig 4 Molded Phenolic Plug for the XM10 Warhead





CONFIDENTIAL




Fig 8 Details of XM5E2 Guided Missile Warhead

CONFIDENTIAL





Fig 9 Details of XM5E2 Guided Missile Warhead

CONFIDENTIAL



~~CONFIDENTIAL~~



CONFIDENTIAL




Fig 12 Ammunition Packing Crate for XM5E2, XM9, and XM10 Guided Missile Warheads (Sheet 1)

CONFIDENTIAL




Fig 14 Ammunition Packing Crate for XM5E2, XM9, and XM10 Guided Missile Warheads (Sheet 3)

CONFIDENTIAL

~~CONFIDENTIAL~~





Fig 15 Field Setup for Static Functioning Tests

~~CONFIDENTIAL~~




Fig 16 External View of Field Setup

~~CONFIDENTIAL~~




Fig 17 Internal View of Field Setup Showing Warhead Positioned in Missile Compartment

~~CONFIDENTIAL~~




Fig 18 Typical Fragment Pattern on Mild Steel Plates Located at 15 Feet




Fig 19 Initial Fragment Velocity for XM5 Warhead with Missile Components

~~CONFIDENTIAL~~

NOTE: The distribution of this report was changed after this distribution list was printed.

DISTRIBUTION LIST

Copy No.

Commanding Officer Picatinny Arsenal ATTN: Technical Information Section Dover, N. J.	1- 5
Chief of Ordnance Dept of the Army ATTN: ORDTU Washington 25, D. C.	6
Armed Services Technical Information Agency Arlington Hall Station Arlington 12, Virginia	7-16
Commanding General Army Rocket & Guided Missile Agency ATTN: ORDXR-RTM	17-18
ORDXR-RM	19-20
ORDXR-IH	21-22
ORDXR-F-NEC	23-24
Technical Library	25-26
Provisional Redstone Ordnance School	27-28
Redstone Arsenal, Alabama	
Commanding General Ordnance Ammunition Command ATTN: ORDLY-AR Joliet, Illinois	29-30
Commanding General ATTN: ORDBG-BRL-T	31
ORDBG-BRL-W	32
Dev and Proof Services	33-34
Ordnance School	35-36
Ordnance Training Command	37-38

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~

DISTRIBUTION LIST

	Copy No.
President	
U. S. Army Air Defense Board	
ATTN: Major Tichenor	39
Capt Johnson	40
Fort Bliss, Texas	
 Commanding General	
White Sands Missile Range	
ATTN: ORDBS-OM	41
ORDBS-EML-W	42
ORDBS-STD	43
Las Cruces, New Mexico	
 Raytheon Manufacturing Company	
ATTN: R. Ling	44
Bedford, Mass	
 VIA: District Chief	
Boston Ordnance District	
Boston Army Base	
Boston 10, Mass	
 Raytheon Manufacturing Company	
ATTN: Documentation Center	45
Andover, Mass	
 VIA: District Chief	
Boston Ordnance District	
Boston Army Base	
Boston 10, Mass	
 Commanding Officer	
Diamond Ordnance Fuze Laboratories	
ATTN: Technica Reference Section	46
ORDTL 06.33	
Conn Ave and Van Ness St, NW	
Washington 25, D. C.	

~~CONFIDENTIAL~~